

### NIT. No.22/ E-Tenders-Works/ICAR-CIRCOT/2023-24

Name of work: Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai.

### **TENDER DOCUMENT**

BID DOCUMENTS(PARTICIPATION THROUGH E-TENDER ONLY)

E-tendering site- www.eprocure.gov.in

## Employer: ICAR- CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY

(INDIAN COUNCIL OF AGRICULTURAL RESEARCH)

Adenwala Road, Matunga, Mumbai-400 019

Ph.022-24127273/76 Fax: 022-24130835, E-mail: director.circot@icar.gov.in

## ICAR-CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY ADNEWALA ROAD, MATUNGA, MUMBAI-400 019.

#### **INDEX**

Name of work: - Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai.

#### NIT No.:22/E-Tender/works/ICAR-CIRCOT/2023-24

| Sr. No. | Description  | Page No. |
|---------|--|----------|
| 1       | Front cover page   | 1        |
| 2       | Index  | 2        |
| 3       | Notice inviting Limited E-tenders.   | 3-4      |
| 4       | Instruction to Bidders (ITB)   | 5        |
| 5       | Online bid submission procedure  | 6        |
| 6       | SECTION-I General Instruction to the Tenderer  | 7-9      |
| 7       | SECTION-II General Conditions of Contract  | 10-15    |
| 8       | SECTION-III - E-Tenderschedule (Important dates and information)   | 16       |
| 9       | List of approved make of materials   | 17-19    |
| 10      | Tender Acceptance Letter (Annexure-I)  | 20       |
| 11      | Instruction for Online Bid Submission (Annexure-II)  | 21-23    |
| 12      | Technical Checklist (Annexure-III)   | 24       |
| 13      | Performa of Agreement (Annexure-IV)  | 25-26    |
| 14      | Financial bid (percentage BOQ) (Bill of quantities and schedule of work) (to be filled and uploaded in financial bid)-Schedule "A" | 27-54    |



# ICAR-CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY (INDIAN COUNCIL OF AGRICULTURAL RESEARCH), ADENWALA ROAD, MATUNGA, MUMBAI-400019.



TEL NO.: 2412 7273/76, 2418 4274/75, 2415 7238

Date: 24.11.2023

#### NOTICE INVITING E-TENDER No. 22/2023-24

The Director, ICAR-Central Institute for Research on cotton Technology, (Indian Council of Agricultural Research), Adenwala Road, Matunga, Mumbai., invites on line Percentage Rate based E-Tenders from approved and eligible contractors registered as contractor of class V minimum in Government organizations namely in CPWD or State PWD by e-tendering process for the following work:-

| 1. | NIT No.   | NIT. No.22/ E-Tenders-Works/ICAR-CIRCOT/2023-24   |
|----|---|---|
| 2. | Name of Work  | Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai. |
| 3. | Estimated cost put to tender  | Rs. 13,63,194/-   |
| 4. | Tender fees (Rs.)   | Rs. 1000/-  |
| 5. | Earnest money deposit   | Rs. 27,300/-  |
| 6. | Period of Completion  | 60 Days   |
| 7. | Bid publish date  | 24/11/2023  |
| 8. | Last Date & Time of<br>submission of e-tender,<br>and other documents as<br>specified in the tender | Date: -13-12-2023 Time: 15.00 hrs.  |
| 9. | Time & Date of Technical bid opening of tender  | Date: 15-12-2023 Time: 10:00 hrs.   |

- 1. The intending bidder must read the terms and conditions carefully. He should submit his bid if he considers himself eligible and he is in possession of all the documents required.
- 2. Information and instruction for bidders posted on website shall form part of bid document.
- 3. The bid document consisting of Plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents can be seen and downloaded from website www.circot.res.in or www.eprocure.gov.in free of cost.

4. Only on-line bids through NIC's e-procurement Portal (CPPP) i.e on <a href="https://www.eprocure.gov.in">www.eprocure.gov.in</a>shall be accepted.

Sujatha Koshy Senior Administrative Officer

#### **INSTRUCTIONS TO BIDDERS (ITB)**

**General:** All bidders must note that this being E-tender, bids received only through E-tendering portal <a href="https://www.eprocure.gov.in">www.eprocure.gov.in</a>.shall be considered as an offer. **Any bid submitted in paper form will not be received and opened and shall be summarily rejected.** 

Further, following instructions should be noted by bidders. Bid Document obtaining process:

Bidders who wish to view free Notification and tender documents can visit ICAR-CIRCOT's website www.circot.res.inOr Central Procurement Portalwww.eprocure.gov.in.

Interested bidders who wish to participate should visit website <a href="www.eprocure.gov.in">www.eprocure.gov.in</a>. which is the ONLY website for bidding their offer. Further, the procedure is as follows:

Register yourself with Central government e-procurement portal for obtaining Login ID and Password. This is one time exercise and applicable for bidding other tenders also.

Obtain Class-III Digital Signature Certificate from any digital signature issuing authority.

Using the login ID, password and digital signature, enter the tender portal to view the tenderdocument.

The bidder can download the tender document from the website: www.eprocure.gov.in

The tender document shall be submitted in online mode through website <a href="www.eprocure.gov.in">www.eprocure.gov.in</a>

Bidder must submit the offer before the online closing date & time. The website will automatically stop accepting the offer after online closing date and time.

Bidder can change quoted rates anytime before of closing date & time.

This tender being E-tender, the digital signature certificate obtained from approved Controller of Certificate Authorities (CCA) shall only be considered as authentic. The process of obtaining digital signature has been specified above.

Tenderer should submit the original Demand drafts for Tender fee and EMD amounts to the institutebefore last date & time of receiving e-tender and get the receipt for the same. In case. Tender fee and EMD arenot received on or before the last date, the offer may be liable to be rejected. Tender fee and EMD amount shall be submitted only through offline modeby Demand draft.

#### **ONLINE SUBISSION OFBIDS**

#### Online Bid SubmissionProcedure

**Tender fee &EMD:** Bidders has to submit Tender fee &EMDoffline through Demand draft submitting to the Institute and get the receipt, scan the receipt and upload the same in the technical bid.

#### **Submission of Technical Bid: (Technical bid cover No.1)**

- A. Technical supporting documents as per Technical bid Checklist (Annexure-III) to be scanned in pdf format and uploaded on the website.
- B. Technical supporting documents including Original Demand drafts in physical form shall be submitted to ICAR-CIRCOT before due date and time and obtain the receipts/acknowledgement for the same.

#### **Submission of Financial Bid:**

Download the attached blank Financial Bid (Financial bid (percentage BOQ).xls), fill up the Blank space with Percentage rate stating above or below and save the details. Do not change the file name. Then upload the Financial Bid in the given link. Do not upload the scan copy of 'Financial Bid' such as pdf or jpg file in document libraryagain.

Bids sent by Telegram, Telex, Cable or Facsimile are not acceptable and will be rejected.

#### Modification and withdrawal ofbids:

The bidder may modify or withdraw his bid after submitting the same prior to the Deadline prescribed for submission of bids.

Bid cannot be modified subsequent to the deadline for submission ofbids.

No bid may be withdrawn in the interval between the deadline for submission of bids and the expiration of the period of bid validity specified by the bidder in the bid form. Withdrawal of a bid during this interval may result in forfeiture of the Bidder's bid security.

#### **SECTION-I**

#### GENERAL INSTRUCTIONS TO THE TENDERER

#### 1.1.0GENERAL

The work is to be executed for the benefit of ICAR-Central Institute for Research on cotton Technology, Adenwala Road, Matunga, Mumbai-400 019.

#### 1.2..0SITE VISIT

The tenderer is advised in his own interest to visit/ examine the site of work before submission of his tender. He may obtain all relevant information that may be necessary for preparation of the bid.

#### 1.3.0TENDER DOCUMENT

- **1.3.1** The tenderer requiring further information or clarification on the tender document may contact the Officer-In-Charge, Engineering Section, ICAR-Central Institute for Research on cotton Technology, up to the closing date, during office hours only.
- **1.3.2** The tenderer must fill their percentage rates in the financial bid form and upload. In Technical bid format please upload all the documents as per Technical check list (Annexure-III). Incomplete tenders submitted which are not as per the instructions are liable to be rejected.
- **13.3**Tenderers may also download the tender documents from ICAR-CIRCOT's website <a href="www.circot.res.in">www.circot.res.in</a> or CPP Portal web site: <a href="www.eprocure.gov.in">www.eprocure.gov.in</a> and upload &submit the e- tenders as per the instructions on <a href="www.eprocure.gov.in">www.eprocure.gov.in</a>

#### 1.4.0MANNER OF SUBMISSION OF E-TENDER

**14.1** The two bid system containing 1) Technical Bid cover 1 which contain technical supporting documents as per the technical checklist (Annexure – III) required to qualify in the technical evaluation, the scanned documents (in pdf format) shall be uploaded on the website one by one during submission 2) Financial bid cover2 (BOQ.xls) (which contain BOQ & Schedule of work (in .xls format) shall be filled on the blank space with name of bidder with address and percentage of rate etc. and uploaded on the web site: <a href="www.eprocure.gov.in">www.eprocure.gov.in</a>, without changing the file name.

#### 1.42Technical Bid Cover 1 (will be pened on the opening day)

Technical Bids cover 1 containing technical supporting document shall be opened first on opening day and bid without necessary of document may liable to be rejected during opening time or during technical evaluation.

## 1.4.3 Financial Bid Cover 2: (only bids of qualified bidders who is qualified in the Technical evaluation process will be opened on later date.)

Financial bid comprising of Microsoft excel file named "BOQ-----xls". Which containing the pages of bill of quantities and schedule of work showing the blank spaces on last below for filling Percentage rates and amounts. The same shall be uploaded for tender submission before last date and time. This should be kept confidential and not to be scanned and uploaded along with documents for technical bid.

#### 1.5.0 SIGNING OF DOCUMENT

All pages of e-tender document including various annexure and Agreement shall be signed and stamped in the physical form by successful bidder on intimation.

#### 1.6.0EARNEST MONEY DEPOSIT (EMD)

- **1.6.1**The tenderer shall pay Earnest Money Deposit along with the tender the sum as indicated in the section- III, in offline form.(D.D. to be drawn in favour of Director, ICAR-CIRCOT, Mumbai.)
- **1.6.2** The Earnest money of the tenderer shall be forfeited to ICAR-CIRCOT without prejudice to any other rights on Remedies.
  - a) If the tenderer withdraws his tender during the period of tender validity specified in the tender document.

- b) If, after acceptance of his tender, the tenderer fails to take up the job.
- c) If, the tenderer fails to sign the contract in accordance with the terms and conditions of the contract.
- d) If, after acceptance of his tender, the tenderer fails to furnish the Performance Guarantee.
- e) If, after acceptance of his tender, the tenderer fails to commence the work within seven days after receipt of work order to that effect.

**1.6.3**The tenders received without the EMD in the prescribed form shall be rejected.

#### 1.7.0PERIOD OF VALIDITY OF TENDER

The tender shall remain valid for 90 days after the date of opening.

#### 1.8.0CARE TO BE TAKEN DURING SUNMISSION OF E-TENDER

**1.8.1**The e- tender duly filled in all respects must be submitted on <a href="www.eprocure.gov.in">www.eprocure.gov.in</a> not later than stipulated time and date as mentioned in Section -III.

#### 1.9.0 OMMISSION AND DECREPANCIES

Should a tenderer find discrepancies in, or omissions from the drawings or any of the tender documents or should be in doubt as to their meaning, he should at once notify the authority inviting the tenders. Who may send a written instruction to all the tenderers. It shall be understood that every endeavor has been made to avoid any error which can materially affect the basis of the tender and the successful tenderer shall take upon himself and provide for the risk of any error which may subsequently be discovered and shall make no subsequent claim on account.

#### 1.10.0 OPENING OF THE TENDER

At the intimated time and date the E-tenders received shall be opened. First the technical bids will be opened in the presence of the intended tenderers and put to evaluation of verification of the eligibility of the bidders and financial bids of only technically qualified bids found during the evaluation of Technical bids will be opened at the later date, which will be intimated to technically qualified bidders. If the opening date is declared a holiday the tenders will be opened on the next working day of the same time.

#### 1.11.0 CANVASSING

Any effort by the tenderer to influence the representatives of ICAR-CIRCOT in making the decision in respect of tender evaluation or award of contract will result in rejection of the e-tender.

#### 1.12.0 RIGHT OF ICAR-CIRCOT TO DEAL WITHTENDERS

**The Director, ICAR-CIRCOT, Mumbai,** reserves the right to accept or reject any e-tender or all the e-tenders at any time prior to award of contract without assigning any reasons whatsoever and no correspondence shall be entertained in this regard.

#### 1.13.0 MISLEADING INFORMATION

If the tenderer/tenderers deliberately gives/give any wrong information or suppresses/any material facts or makes/make false representations in this tender or creates/create circumstances for the acceptance of his/their tender, ICAR-CIRCOT reserves the right to reject such tender at any stage or cancel the order even after acceptance of the tender at the risk and cost of the tenderer/tenderers.

#### 1.14.0 AWARD OF WORK

ICAR-CIRCOT will notify the successful tenderer in writing by a registered letter to confirm that his tender has been accepted.

#### 1.15.0 SIGNING OF CONTRACT

The successful tenderer has to sign the agreement on non-judicial stamp paper of value Rs.100/- within 15 days from the receipt of offer of contract. The tenderer has to arrange the stamp paper at his cost.

#### 1.16.0PERFORMANCE GUARANTEE

- The successful tenderer has to pay 10% of the tendered amount as Performance Guarantee in the form of Demand Draft payable to "The Director, ICAR-CIRCOT, Mumbai" before commencing the work.
- **1.16.2** Performance Guarantee shall be treated as Security deposit after completion of work and shall be refunded after 360 days from the date of successful completion of the job.

#### 1.17.0COMPLETION OF WORK AND PENALTY FOR DELAY IN COMPLETION.

- 1.17.1 All the work items as per the enclosed shall be completed positively within 40 days from the date of agreement.
- **1.17.2** Any willful delay on the part of the contractor in completing the construction within the stipulated period will render him liable to pay liquidated damages @ 1.5% of the tendered amount per month of delay to be computed on per day basis will be charged and deducted from payments due to him. The ICAR-CIRCOT may cancel the contract and take recourse to such other action as deemed appropriate once the total amount of liquidated damages exceeds 2% of the contract amount. (Note: The amount of liquidated damages per day should be determined at 0.05% of the contract value of the works).

#### 1.18.00THERINFORMATION

**1.181** Non-compliance with any of the conditions set forth here above is liable to result in the tender being rejected.

**1.18.2** The tendered works are not to be subletting to other contractor which will leads to cancellation of contract.

#### **SECTION-II**

#### GENERAL CONDITIONS OF CONTRACT

#### CLAUSE 1: EXECUTION OF CONTRACT DOCUMENT

- 1.1 The tenderer whose tender is accepted shall be required to appear at the ICAR-CIRCOToffice in person to execute the contract documents after receipt of work order.
- 1.2 Every contract shall be completed in respect of the documents it shall constitute.
- 1.3 The tenderer shall quote his percentage rates complying with the instructions contained in the tender documents. The items quantities shown in the tender schedule are given as a guide and are approximate only and are subject to variation according to the needs of ICAR-CIRCOT. The ICAR-CIRCOT does not also guarantee work under each item of the schedule. No correspondence shall be entertained in this regard. The Quoted Percentage rates should be inclusive of all cost of materials, labor charges, carriages, all taxes whatsoever, storage, watch and ward, wastages etc. The quoted rates shall not be increased under any circumstances.
- 1.4The tenderer shall keep the offer open for a minimum period of **90 days** from the date of opening of tenderer the period extended further by mutual consent from time to time.
- Works are required to be completed strictly within the time and date stipulated in the tender document.
- 1.6 The tenderer shall not take the advantage of any misinterpretation of the conditions due to typing or any othererror/errors and if any doubt, shall bring such error/errors to the notice of ICAR-CIRCOT without delay.

#### **CLAUSE 2: COMMENCEMENT OF WORK**

The contractor shall commence the works on site as per the date mentioned in work order. Thereafter the contractor shall proceed with the works with due expedition to complete the works within the stipulated time period.

#### **CLAUSE 3: TENDERED RATES**

- 3.1 The tendered rates shall be inclusive of all taxes and cases, and also inclusive of tax levied in respect ofwork contract under provision of GST.
- 3.2 The rates quoted by the contractor must be inclusive of GST. No extra payment on this account will be made to contractor. The quoted rates must be valid for 90 daysfrom the date of opening of tender.
- 3.3 The contractor must visit the site and study the working conditions, site conditions, and the quantum of workinvolved before quoting the rates for lump sum items. No claim of the contractor shall be entertained in under estimation of Lump sum items.
- 3.4 The quantities of work items may increase or decrease at the time of executive of work and percentage quoted by the tenderer will be same for all quantities.

#### **CLAUSE 4: EARNEST MONEY DEPOSIT**

- 4.1 Earnest Money deposit Original Demand draft shall be submitted to Institute before due date and obtain the receipt for the same and scanned copy of receipt may be uploaded in the e-tender, the tenderer who do not deposit the EMD in the form shall summarily rejected. The tenderer who deposit EMD less than the prescribed amount shall be rejected.
- 4.2 The Earnest money deposit Demand drafts of the Unsuccessful tenderers will be returned to the bidders on deciding about acceptance or other wise of the tender, or Expiry of the period of tender validity, whichever is earlier (minimum 10-15 days and maximum up to the completion of tender validity period).
- 4.3The Earnest money of the tenderer shall be forfeited to ICAR-CIRCOT without prejudice to any other rights or Remedies.
- (a) If the tenderer withdraws his tender during the period of tender validity specified in the tender document.

- (b) If, after acceptance of his tender, the tenderer fails to take up the job.
- (c) If, the successful tenderer fails to sign the contract in accordance with the terms and conditions of the contract.
- (d) If, after acceptance of his tender, the successful tenderer fails to furnish the required amount of performance Guarantee.
- (e) If, after acceptance of his tender, the successful tenderer fails to commence the work within seven days from the date of receipt of work order to that effect.

#### CLAUSE 5: PERFORMANCE GUARANTEE (PG)/SECURITY DEPOSIT (SD)

- 5.1 The successful tenderer has to deposit an amount equal to 10% of the tendered value, in the form of crossed Demand Draft drawn in favor of "The Director, ICAR-CIRCOT, Mumbai", towards performance guarantee after receiving the work order.
- 5.2 Commencement of work shall be permitted only after the receipt of performance guarantee. The Performance Guarantee will be treated as Security Deposit after completion of work
- 5.3 If the successful tenderer fails to deposit the performance guarantee within 15 days from the date of receipt of work order, it will be presumed, that, the contractor is not interested in the contract and the offer of contract shall be cancelled and the EMD of the contractor will be forfeited.
- 5.4 If any time before the Performance Guarantee /security deposit or any part thereof is refunded to the contractor, it shall appear to Engineer-In-charge or his subordinate in charge of the work, that any work has been executed with unsound, imperfect or unskillful workmanship or with materials of inferior quality, or that any materials or articles provided by him for the execution of the work are unsound, or of quality inferior to that contracted for, or are otherwise not in accordance with the contract it shall be lawful for the Engineer-in-charge to intimate this fact in writing to the contractor and then notwithstanding the fact that the work, materials or articles complained of may have been inadvertently passed, certified and paid for, the contractor shall be bound forthwith to rectify, or remove and reconstruct the work so specified in whole or in part, as the case may require. or if so required, shall remove the materials or articles so specified and provided & other proper and suitable materials or articles at his own charge and cost, and in the event of his failing to do so within a period to be specified by the Engineer-in-charge in the written intimation aforesaid, the contractor shall be liable to pay compensation at the rate of one percent on the amount of the estimate for every day not exceeding ten days during which the failure so continues and in the case of any such failure the Engineer-in-charge may rectify or and remove, re-execute the work or remove and replace the materials or articles complained of as the case may be at the risk and expense in all respects of the contractor. Should the Engineer-in-charge consider that any such inferior work or materials as described above may be accepted or made use of it shall be within his discretion to accept the same at such reduced rates as he may fix therefore.
- 5.6 The Performance Guarantee /Security Deposit shall be released after 360 days from the date of successful completion of the job.
- 5.7 If the contractor fails to rectify the defects even after the receiving written instructions from ICAR-CIRCOT, such works shall be done departmentally, and the expenditure shall be deducted from the security deposit of the contractor.

#### **CLAUSE 6: LABOUR ACT**

- No contractor shall employ any person who is under the age of 18 years. Engineer In charge is authorized to remove from work any person who is below 18 years.
- 6.2 The contractor shall pay fair and reasonable wages to the workmen employed by him, in the event any disputearising between the contractor and his workmen on the ground that the wages paid are not fair and reasonable, the dispute shall be referred without any delay to the Director, ICAR-CIRCOT, Mumbai. The decision of the Director, ICAR-CIRCOT, shall be conclusive and binding on the contractor.

- All facilities provided in the contract labour act should be provided (Regulation and Abolition Act 1971).
- The contractor shall pay fair and reasonable wages as per the minimum wages act (Govt. of India/ Govt. of Maharashtra, whichever is highest) prevailing in the locality.
- 6...5 The contractor shall duly comply all provisions of contract labour act(Regulation and Abolition) 1979 andMaharashtra contract labour (Regulation and Abolition) rules 1971, as amended from time to time and all other relevant status and statutory provision concerning payment of wages particular to the workmen employed on the site.

#### **CLAUSE 7: SAFETY OF THE WORKERS**

- 7.1 The contractor shall be responsible for and shall pay any compensation to his workmen under the Workmen's compensation act 1923 (VIII of 1923) (hereafter call the said act) for injuries caused to the workmen.
- 7.2 The contractor shall be responsible for and shall pay the expenses or providing any medical aid to any Workman who may suffer bodily injury as a result of an accident.
- 7.3 The contractor shall provide all necessary personal safety equipment and first aid apparatus available for theuse of workers employed on the site and shall maintain the same in condition suitable for immediate use at any time and shall comply with following regulations in connection therewith
  - The workers shall be required to use the equipment so provided by the contractor and the contractor shall take adequate steps to ensure proper use of the equipment by those concerned.
  - (a) When work is carried on in proximity to any place where there is risk or drawing all necessary equipment shall be provided and kept ready for use and all necessary steps shall be taken for prompt rescue of any person in danger
  - (b) Adequate provisions shall be made for first aid treatment of all injuries likely to be sustained during thecourse of work

#### **CLAUSE 8: MODE OF PAYMENT**

- 8.1 The payment of R.A/Final bills will be made as per the certificate of Engineer in charge of the work for releasing the bills against the work items completed and measured by him. The contractor should submit his billsas per the directions of the Engineer in charge and same will be paid within a month if it is in order. i.e. 1) 1 st R.A. Bill admissible only after completion of 50% of the work order amount, for which 25% of the tender
  - 1) 1 st R.A. Bill admissible only after completion of 50% of the work order amount, for which 25% of the tender amount will be released against the R.A. bill above.
  - 2) IInd R.A. Bill admissible only after completion of 75% of the work order amount, for which 50% of the tender amount will be released against the R.A. bill above.
  - 3) IIIrd R.A. Bill admissible only after completion of 90% of the work order amount, for which 80% of the tender amount will be released against the R.A. bill above.
  - 4) IVth & Final Bill admissible only after 100% completion of work accompanied by completion Certificate from Engineers In-Charge, for which remaining 20% balance amount will be released.
- 8.2 On Final completion of the work the contractor shall be furnished with a certificate by the Engineer-Incharge(Works) of such satisfactory completion. But no such certificate shall be given nor shall the works be considered to be complete until the contractor shall have removed all the rubbish, surplus material, all scaffolding, etc. from the premises. The bill forwarded by the contractor shall be considered for payment only after obtaining the certificate as described above.
- 8.3 All payments for the work will be made through E transfer only. The contractors shall provide correct Bank details along with bill itself.
- 8.4Regarding all payments, inquiry shall be made only to the Engineer-Incharge of the work.

#### **CLAUSE 9: TECHNICAL SPECIFICATIONS**

- In the contractor shall execute the whole and every part of the work in the most substantial and workmanlikemanner, and both as regards material and every other respect in strict accordance with specifications as mentioned in the tender document against each job.
- 9.2 Every effort has been made to give detailed specifications for each and every item in the schedule; however, wherever specifications mentioned by ICAR-CIRCOT are not sufficient, the works should be carried out as per CPWD technical specification and works manual with latest correction slip.
- 9.3 In general, all the works should be carried out conforming to ISI test standards and specifications. All thematerials used in construction shall confirm to the requirement of latest IS specifications
- 9.4 The Engineer-In charge shall have power to make any alterations in or additions to the original specifications, drawings, designs, and instructions that may appear to him to be necessary or advisable during the progress of the work and the contractor shall be bound to carry out the work in accordance with any instructions in this connection which may be given to him in writing signed by the Engineer-Incharge and such alteration shall not invalidate the contract. Payment of such additional works which are not included in the quantities and rates of original tender schedule shall be made on the basis of CPWD Delhi schedule (2021) rates and procedures. Where, however, the work is to be executed according to the designs, drawing and Specifications recommended by the contractor and accepted by the competent authority of ICAR-CIRCOT, the alterations above referred to shall be within the scope of such designs, drawings and specifications appended to the tender.
- 9.5 The successful contractor shall make his own arrangement to obtain all materials required for the work like cement, sand, water, electricity, etc.
- 9.6 Samples of all vital materials like Granite, Plywood, Tiles, Locking systems, Glass, Bricks, Taps, etc, are tobe approved by the Engineer-in-charge(Works), ICAR-CIRCOT, Mumbai. The tenderer has to bear the cost of samples.
- 9.7 In all cement involved works 53 grade cement to be used.
- 9.8 Wall paint **ASIAN PAINTS APEX** to be used.

#### .CLAUSE 10: UNSATISFACTORY AND DEFECTIVE WORKS

- 10.1 Defective work is liable to be rejected at any stage. The contractor on no account can refuse to rectify the defects merely on reasons that the further work has been carried out. No extra payment shall be made for rectification.
- 10.2 If the progress of any particular portion of the work is unsatisfactory, the engineer In-charge shallNotwithstanding that the general progress of the work, be entitled to take action after giving the contractor 10 day notice in writing. The contractor will have no claim for compensation, for any loss sustained by him owing to such action

#### **CLAUSE 11: INCOMETAX DEDUCTION**

11... 1. TDS (Tax Deducted at Source) will be as per prevailing rules and regulations of Income Tax Department.

#### **CLAUSE 12: ELECTRICITY AND WATER**

**1.2.1** The contractor has to make his own arrangements for water and electricity. Use of BMC water from any source in the campus is strictly prohibited.

#### **CLAUSE 13: DAMAGES TO GOVT.PROPERTY**

- 13.1 Compensation for all damages done intentionally or unintentionally by contractor's labor whether in orbeyond the limits of Govt. property including any damage caused by spreading of fire, shall be estimated by the Engineer in-charge subject to the decision of the Director, ICAR-CIRCOT, on appeal shall be final and the contractor shall bound to pay the amount of the assessed compensation on demand, failing which, the same will be recovered from the bill of the contractor.
- 13.2 The contractor shall be responsible for making good the damages done to the existing property or work during construction by his men

#### CLAUSE 14: SUPERVISION AND INSPECTION OF WORKS AND QUALITY CONTROL

#### (a) SUPERVISION

The contractor shall either himself supervise the execution of the works or shall appoint the competent engineer approved by the Engineer-in-charge, to act on his behalf. If in the opinion of the Engineer-in-charge, the contractor has himself no sufficient knowledge and experience of receiving instructions or cannot give his full attention to the works, the contractor shall at his own expenses, employ as his accredited agent a qualified Engineer approved by the Engineer-in-charge. If the contractor fails to appoint a suitable agent, the engineer –Incharge will suspend the works until a suitable agent is appointed and the contractor shall be responsible for the delay so caused to the works and the contractor shall not be entitled for any compensation on this behalf

#### (b) INSPECTION

The contractor shall inform the Engineer-in-charge in writing when any portion of the work is ready for inspection giving him sufficient notice to enable him to inspect the same without affecting the further progress of the work. The work shall not be considered to have been completed in accordance with the terms of contract until the Engineer-in-charge shall have certified in writing to that effect. Approval of materials of workmanship of approval of part of the work during the progress of execution shall not bind the Engineer-incharge or in any way affect him even to reject the work which is alleged to be completed and suspend the issue of his certificate of completion until such alternations and modifications or reconstruction's have been effected at the cost of the contractor as shall enable him to certify that the work has been completed to his satisfactions. The contractor shall provide at his cost necessary ladders and such arrangements as to provide necessary facilities and assistance for proper inspection of all parts of the work at his own cost.

#### **CLAUSE 15: MODE OF MEASURMENT**

- (a) All measurements will be recorded in MKS / SI units, with an accuracy up to plus or minus one centimeter. CPWD method of measurement shall be adopted for taking measurements.
- (b) Measurement of each and every item will be recorded on the day of its actual execution. The measurements shall be recorded in the presence of the contractor or his authorized agent. The measurements recorded by the site engineer shall be final and binding on the contractor in case they remain absent during the measurement. No correspondence shall be entertained in this regard.
- (c) Measurements area of granite, tiles, marble, Aluminum sections, etc shall be taken on clear cut exposed areas only.
- In addition to above, the normal CPWD mode of measurement will be adopted wherever ICAR-CIRCOT, terms and conditions on this account are not sufficient.
- Where for proper measurements of the work, it is necessary to have an initial set of levels or other measurements taken, the same recorded as in the authorized field book, measurement book of Government by the Engineer-in-charge or his authorized representative will be signed by the contractor who will be entitled to have a true copy of the same made at his cost. Any failure in the part of the contractor to get such levels etc. recorded before starting the work will render him liable to accept the decision of the Engineer-in-charge as to the basis of taking measurements. Likewise the contractor will not cover any work which will render its subsequent measurement difficult or impossible without first getting the same jointly measured by him and authorized representative of the Engineer Incharge. The record of such measurements on the Government side will be signed by the Contractor and he will be entitled to have a true copy of the same at his cost.

#### **CLAUSE 16: SAMPLES AND TESTING OF MATERIALS**

- All materials to be used on the work shall be got approved from the Engineer in Charge and shall pass the test or analysis required by him which will be;
  - (a) As specified in the specification for the items.

- (b) B.I.S, specifications for the items.
- (c) Such recognized specifications acceptable to Engineer-in-charge as equivalent thereto or in absence of such authorized specification. Such requirement test and/or analysis as may be specified by the Engineer-in-charge in order of precedence given above.

The contractor shall at his risk and cost make all arrangements /or shall provide for all such facilities as the Engineer-in-charge may require for collecting, preparing required number of samples for tests or analysis at such time and to such places as may be directed by Engineer and bear all such charges. Such samples shall also be deposited with the Engineer-in-charge

The contractor shall, if and when required, submit at his cost the samples of the materials to be tested or analyzed and if so directed, shall not make use of incorporate in the works any material to be represented by the samples until the required test or analysis have been made and the materials finally accepted by the Engineer-in-charge.

The contractor shall not be eligible for any claim or compensation either arising out of any delay in the work or due to any corrective measure required to be taken on account of and as a result of testing of the materials.

In case of materials procured by the contractor, testing as required by the codes and specifications shall be arranged by him at his own cost. Testing shall be done in the presence of authorized representative of the Engineer-in-charge at the nearest approved laboratory. In addition testing other than as required by specification is ordered the testing charges, shall be done the Department, if she the last results are satisfactory and by the contractor if the same are not satisfactory

#### **CLAUSE 17: CLAIMS**

- 17.1 No extra work shall be done without the written permission of Engineer In charge. No claim of extra workshall be paid separately.
- 17.2 Claims for any extra work shall be registered within 30 days of occurrence of the event along with final bill. No separate bill shall ever be made for any additional or extra works done. ICAR-CIRCOT shall not be responsible if the contractor executes any extra work without written order

#### **CLAUSE 18: HANDING OVER OF WORK:**

18.1 All the works and materials before final taken over by Government, will be the entire liability of the Contractor for guarding, maintaining and making good any damages of any magnitude, interim payments made for such work will not alter this position. The handling over the contractor and taking over by the Executive Engineer or his authorized representative will be always in writing of which copies will go to Executive Engineer or his authorized representative and the contractor, it is however understood that before taking over such work Govt, will not put into regular use of distinct from casual or incidental one, except as specifically mentioned elsewhere in this contract or as mutually agreed to.

#### **CLAUSE 19: OTHER CONDITIONS**

- 19.1 No work shall be done on Sunday and other holidays without the prior permission in writing of the Engineer-Incharge.
- 19.2 Any contractor who does not accept these conditions shall not be allowed to tender for works.
- 19.3The contractor shall not sublet or assign his contract to others.
- 19.4 Except where otherwise specified in the contract the decision of the Director, ICAR-CIRCOT, Mumbai, shall be final and binding on all parties of the contract upon all questions relating to the meaning of the specifications, designs, drawings, etc, or as to any other question, claim, right, matter, or thing whatsoever, in any way arising out of, or relating to the contract, design, drawing, specifications, etc, or otherwise concerning the works, or the execution, or failure to execute the same, whether arising, during the progress of the work, or after the completion, or abandonment thereof.
- 19.5 If the contractor stops the work in between due to his personal reasons, financial grounds, etc, for more than ten days after the commencement of works, the competent authority of ICAR-CIRCOT shall issue a notice to the contractor to this effect. The contractor has to execute the works within seven days from the date of receipt of the notice, failing which the contract will be terminated, and incomplete works will be executed by some other party at the risk and cost of the contractor. The decision of the Director, ICAR-CIRCOT Mumbai, will be final in this regard without prejudice to any other rights or remedies whatsoever.

## ICAR-CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY ADNEWALA ROAD, MATUNGA, MUMBAI-400 019.

#### **SECTION-III**

### **E-TENDER SCHEDULE**

#### IMPORTANT DATES AND INFORMATION

| S.No. | Details of Schedule  | Date & Time/ Information   |  |
|-------|--|--|--|
| 1     | Name of Work:  | Yashwantrao Chavan Building- Renovation of Guest<br>House room no. 10, Second floor of Yashwantrao<br>Chavan Building at ICAR- CIRCOT, Matunga,<br>Mumbai. |  |
| 2     | Estimated Cost:  | Rs. 13,63,194/-  |  |
| 3     | NIT NO.  | NIT. No.22/ E-Tenders-Works/ICAR-CIRCOT/2023-24  |  |
| 4     | Web site for Uploading of e-<br>tenders for this work                  | www.eprocure.gov.in only.  |  |
| 5     | Date and web sites for start of<br>Downloading of E-tender<br>document | Please refer Tender details published for the work on following site.  www.circot.res.in or www.eprocure.gov.in  |  |
| 6     | Last date and time for<br>Downloading of E-tender<br>document          | Up to 11.00 hrs on 13 Dec, 2023  |  |
| 7     | Last date of Receipt of Online tenders                                 | Up to 15.00 hrs on 13 Dec, 2023  |  |
| 8     | Opening of tenders (Technical bids only)                               | At 10:00 hrs on 15 <sup>th</sup> Dec, 2023   |  |
| 9     | Opening of Tenders (Financial bids)                                    | Date and time of financial bid opening can be intimated later after the technical evaluation of technically admitted bids                                  |  |
| 10    | Validity of tender and time for completion of work                     | 90 days from the date of opening of tender, 60 days from commencement date.  |  |
| 11    | Earnest money deposit amount   | Rs. 27,300/- through Demand draft to be submitted to Institute before due date.  |  |
| 12    | Tender fee amount  | Rs.1000/- through Demand draft to be submitted to Institute before due date.   |  |
| 13    | Intimation of Corrigendum, if any                                      | Will be notified on websites only.   |  |

#### LIST OF APPROVED MAKE OF MATERIALS

#### (FOR CIVIL WORKS)

Specification/brands names of materials (Refer materials, whichever are applicable for the scope of work) and finishes approved by the Engineer-in-Charge are listed below. However approved equivalent materials and finishes of any other specialized firms may be used, in case it is established that the brands specified below are not available in the market and subject to approval of the alternate brand by the Engineer-in-Charge.

|    | Aluminium Sections  | Jindal, Hindaloc, Indalco   |
|----|---|---|
| 31 | Friction Stay Hinges  | Earl-Bihari   |
| 32 | Nuts, Bolts and Screws, Steel                                 | Kundan, Priya, Atul   |
| 33 | EPDM Gasket   | Hanu/Anand  |
| 34 | Structural Silicone   | Dow Corning/Wacker  |
| 35 | Weather Silicone  | Dow Corning/Wacker  |
| 36 | Adhesive Tape   | Norton  |
| 37 | Terrazzo Tiles (Precast)/Plain/                               | NITCO, HINDUSTAN, MODERN  |
|    | Chequerred  |   |
| 38 | Glazed Ceramic Tiles  | JOHNSON, SOMANY, KAJARIA, BELL CERAMICS, NITCO, ORIENT, ASIAN   |
| 39 | Cement Concrete Tiles/Hardonite Tiles                         | NITCO, NTC, HINDUSTAN   |
| 40 | Vitrified Tiles   | GRANITO, NAVIN DIAMOND, KAJARIA, JOHNSON(MARBONITE),<br>ORIENT, ASIAN   |
| 41 | Tile Adhesive70.  | CICO, PIDLITE FERROUS   |
| 42 | Clay Tiles on Roof  | KENZAI, JOHNSION  |
| 43 | C.C. Pavers   | NITCO-(ROCKARD), TUFTEK, K.K, ESS&ESS, MODERN   |
| 44 | Acrylic Exterior Paint  | SNOWCEM(Trump), ASIAN(Apex), ICI(Weather shield), NEROLAC(surksha plus), BERGER(weathercoat), SHALIMAR (XTRA) |
| 45 | Grass Paver   | Unistone, Ultra, Shree, Supertile, Modern   |
| 46 | Water-Proof Cement Paint                                      | Snowcem, Kilicknixon, Durocem, Berger, ICI India Ltd., Shalimar   |
| 47 | Synthetic Enamel Paint  | Berger(Luxol High Gloss), Nerolac, Asian(apcolite),ICI India Ltd.(Dulux Gloss), Shalimar (Superlac)           |
| 48 | Plastic Emulsion Paint  | Berger(Rangoli), Nerolac, ICI India Ltd.(Dulux),<br>Asian (Premium)   |
| 49 | Vitreous China Sanitaryware                                   | Parryware, Hindware, CERA   |
| 50 | Fireclay Sinks & Drain Boards                                 | Parry, Sunfire  |
| 51 | Stainless Steel Sinks   | Nilkanth, AMC, Cobra, Jayana, Franky  |
| 52 | C.P. Brass Fittings   | Prima, Marc, Kingston   |
| 53 | Soil, Waste & Vents Pipes & Fittings<br>Centrifugal Cast Iron | Neco, RIF   |
| 54 | LA (CI) Pipes   | RIF, Neco   |
| 55 | G.I. Pipes  | Tata, Jindal – Hissar   |
| 56 | G.I. Fittings (Malleable Cast Iron)                           | Unik, ICS, Neo  |
| 57 | Gunmetal Valves   | Leader, Sant, Zoloto  |
| 58 | Stone Ware Pipe & Gully Traps                                 | Perfect, Parry  |
| 59 | R.C.C. Pipes-(NP-2)   | Lakshmi, Sood&Sood, Jain & Co.  |
|    |   |   |
| 60 | MS Pipe   | Kesoram, Electro Steel  |
| 61 | C.I. Double Flanged Sluice Valves                             | Kirloskar, IVS, Burn  |

| 62 | C.I. Double Flanged Non Return<br>Valves           | Kirloskar   |
|----|--|---|
| 63 | C.I. Manholes Covers                               | B.C. RIF  |
| 64 | Upvc Pipe  | Supreme, Prince, Finolex  |
| 65 | Copper Tubes/Pipes                                 | Rajco, Max Flow ABC   |
| 66 | Copper Fittings                                    | Yorkshine, IBP, Bconex  |
| 67 | Ball Valves  | Zoloto, IBP, Arco   |
| 68 | Butterfly Valves                                   | Audco   |
| 69 | Unglazed Vitrified Tiles                           | Johnson – (Endura), Somany – (Dura Stone),<br>Regency – (Tiles)       |
| 70 | Spider Fittings                                    | . Dorma, Sevax  |
| 71 | Mineral Fibre False Ceiling                        | Armstrong or Equivalent as per Relevant Is Codes                      |
| 72 | . APP  | Roflex, STP ,Dermabit, Watertite(Alex Extrusions Limited)             |
| 73 | PE-AL-PE PIPES & FITTINGS                          | JINDAL, SUPREME   |
| 74 | PVC/SINTHETIC WATER TANK                           | SINTEX, UNIPLAST, SPL   |
| 75 | SELF CLOSING PILLAR TAPS                           | JAQUAR  |
| 76 | . HOT WATER INSULATION                             | GLASS WOOL/ MINERAL WOOL  |
| 77 | ELASTOMERIC SLEEVE                                 | UP TWIGA / ROCKLLOYD  |
| 78 | BEVELLED EDGE MIRROR                               | ATUL/SAINT GOBAIN/MODI  |
| 79 | ROLLING SHUTTERS                                   | RAMA ROLLING SHUTTERS / JOYTI ROLLING/ ANAND INDUSTRIES SHUTTERS      |
| 80 | WALL PUTTY   | BIRLA, J.K, BERGER, SHALIMAR  |
| 81 | DRAPERY ROD, VENETIAN BLINDS                       | MAC, VISTA  |
| 82 | RMC  | ACC, Unitech, Ultra Tech (Birla), L&T, A-1 and NDCON                  |
| 83 | PTMT Fittings                                      | Prayag, Polytuff  |
| 84 | Distemper  | Berger (Bison), Asian (Tractor), ICI (Maxiiite),<br>Neroalc (Nerolac) |
| 85 | PVC Flushing Cistern 5 litre/ 10 litre<br>Capacity | Hindware, Perryware, Cera   |
| 86 | Metal ceiling tiles                                | Armstrong, SaintGobin&Anutone.  |

Note:

Makes other than specified above (if necessary) shall be approved by the Engineer in charge of the work.

### TENDER ACCEPTANCE LETTER (To be given on Company Letter Head)

[Department User may ask for Tender Acceptance Letter instead of asking Signed Tender Document from the Bidders. This is a sample format, User may revise it as per their Tender Conditions]

Date:

To,
The Director
ICAR-Central Institute for Research on cotton Technology
Adenwala Road,
Matunga, Mumbai.

Sub: Acceptance of Terms & Conditions of Tender

Tender Reference No: NIT.No.22/E-Tenders-works/ICAR-CIRCOT/2023-24

Name of Tender/Work: - Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai

Dear Sir,

- 1. I/We have downloaded / obtained the tender document(s) for the above mentioned 'Tender/Work' from the web site(s) namely: Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai as per your advertisement, given in the above mentioned website(s).
- 2. I /We hereby certify that I / we have read the entire terms and conditions of the tender documents from **Page No. 1 to 54** (including all documents like annexure(s), schedule(s), etc), which form part of the contract agreement and I / we shall abide hereby by the terms / conditions / clauses contained therein.
- 3. The corrigendum (s) is sued from time to time by your department/organization to ohave also been taken into consideration, while submitting this acceptance letter.
- 4.I/Weherebyunconditionallyacceptthetenderconditionsofabovementionedtenderdocument(s)/corrigendum(s) in its totality / entirety.
- 5.I/WedoherebydeclarethatourFirmhasnotbeenblacklisted/debarredbyanyGovt. Department/Public sector undertaking.
- 6. I / We certify that all information furnished by theour Firm is true & correct and in the event that the informationisfoundtobeincorrect/untrueorfoundviolated,thenyourdepartment/organisationshall without giving any notice or reason therefore or summarily reject the bid or terminate the contract, without prejudicetoanyotherrightsorremedyincludingtheforfeitureofthefullsaidearnestmoneydeposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)

#### **Annexure-II**

#### **Instructions for Online Bid Submission**

## (Department user may attach this Document as an Annexure in their Tender Document which provides complete Instruction for online bid submission for Bidders)

The bidders are required to submit soft copies of their bids electronically on the CPP Portal, using valid Digital Signature Certificates. The Instructions given below are meant to assist the bidders in registering on the CPP Portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP portal.

More information useful for submitting online bids on the CPP Portal may be obtained at:https://eprocre.gov.in/eprocure/app

#### REGISTRATION

- 1) Bidders are required to enroll on the e-Procurement module of the Central Public Procurement Portal (URL: <a href="https://eprocure.gov.in/eprocure/app">https://eprocure.gov.in/eprocure/app</a>) by clicking on the link "Online bidder Enrolment" on the CPP Portal which is free of charge.
- 2) As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for their accounts.
- 3) Bidders are advised to register their valid email address and mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.
- 4) Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (Class III Certificates with signing key usage) issued by any certifying Authority recognized by CCA India (e.g.Sify/nCode/eMudhra etc.), with their profile.
- 5) Only one valid DSC should be registered by a bidder. Please note that bidders are responsible to ensure that they do not lend their DSC's to others which may lead to misuse.
- 6) Bidder then logs in to site through the secured log-in by entering their user ID/password and the password of the DSC/e-Token.

#### **SEARCHING FOR TENDER DOCUMENTS**

- 1) There are various search built in the CPP Portal, to facilitates bidders to search active tenders by several parameters. These parameters could include Tender ID, Organization Name, Location, Date, Value, etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as Organization Name, Form of Contract, Location, Date, Other Keywords etc. to search for a tender published on the CPP Portal.
- 2) Once the bidders have selected the tenders they are interested in, they may download the required documents/ tender schedules. These tenders can be moved to the respective 'My Tenders" folders. This would enable the CPP portal to intimate the bidders through SMS/e-mail in case there is case there is any corrigendum issued to the tender document.
- 3) The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification / help form the Helpdesk.

#### PREPARAION OF BIDS

- Bidder should take into account any corrigendum published on the tender document before submitting their bids.
- 2) Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.
- 3) Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document / schedule and generally, they can be in PDF/XLS/ RAR/DWF/JPG formats. Bid documents may be scanned document.
- 4) To avoid the time and effort required in uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN card copy, annual reports, auditor certificates etc.) has been provided to the bidders. Bidders can use "May Space" Other important Documents" area available to them to upload such documents. These documents may be directly submitted form the "My Space" area while submitting a bid, and need not be uploaded again and again. This will lead to reduction in the time required for bid submission process.

Note: My Documents space is only a repository given to the Bidders to ease the uploading process. If Bidder has uploaded the Documents in My Documents space, this does not automatically ensure these Documents being part of Technical Bid.

#### SUBMISSION OF BIDS

- 1) Bidder should log into the site well in advance for bid submission so that they can upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other issues.
- 2) The bidder has to digitally sign and upload the required bid documents one by on as indicated in the tender document.
- 3) Bidder has to select the payment option as "offline" to pay the tender fee / EMD as applicable and enter details of the instrument.
- 4) Bidder should prepare the EMD as per the instructions specified in the tender document. The original should be posted/couriered / given in person to the concerned official, latest by the last date of bid submission or as specified in the tender documents. The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise the uploaded bid will be rejected.
- 5) Bidders are requested to note that they should necessarily submit their financial bids in the format provided and no other format is acceptable. If the price bid has been given as a standard BOQ format with the tender document, then the same is to be downloaded and to be filled by all the bidders. Bidders are required to download the BoQ file, open it

ad complete the white coloured (unprotected) cells with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it and submit it online, without changing the filename. If the BoQ file is found to be modified by the bidder, the bid will be rejected.

- 6) The server time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The bidders should follow this time during bid submission.
- 7) All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorized persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage encryption of sensitive fields is done. Any bid document that tis uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using/nod opener's public keys. Overall the uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- 8) The uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- 9) Upon the successful and timely submission of bids (i.e. after Clicking "Freeze Bid Submission in the portal), the portal will give a successful bid submission message &a bid summary will be displayed with the bid no. and the date & time of submission of the bid with all other relevant details.
- 10) The bid summary has to be printed and kept as an acknowledgment of the submission of the bid. This acknowledgement may be used as an entry pass for any bid opening meetings.

#### **ASSISTANCE TO BIDDERS**

- Any queries relating to the tender document and the terms and conditions contained therein should be addressed to the Tender Inviting Authority for tender or the relevant contact person indicated in the tender.
- 2) Any queries relating to the process of online bid submission or queries relating to CPP Portal in general may be directed to the 24X7 CPP Portal Helpdesk.

Scan copy of the document to prove that applicant has achieved a minimum annual value of turnover of Rs.------(1.5 times estimated cost) carried out in any of the years over the last 7 years period, ending 31 March previous year.

This is as per MANUAL FOR PROCUREMENT OF WORKS 2019, Page 27)

#### Annexure\_III

## TECHNICAL BID CHECKLIST: (List of technical documents required to be uploaded in Technical bid cover No.1)

The following Technical supporting documents (for eligibility) are to be uploaded in pdf format on website: <a href="www.eprocure.gov.in">www.eprocure.gov.in</a>. Later all original D.D to be submitted to the Institute in physical form dulymentioning the tender reference,

- i) Scan copy of Original D.D for EMD (in pdf format)
   (Refundable) (Submit the original D.D to office and get the Receipt on submission before date of opening of Technical bids of e-tender)
- ii) Scan copy Original D.D.for Tender fee (in pdf format) (nonrefundable) (Submit the original D.D to office and get the Receipt on submission before date of opening of Technical bids of e-tender)
- iii) Scan copy of Letter of undertaking of offer (as per Annexure-1)(in pdf format)
- iv) Scan Copy of Registered contractor of class V minimum in Government organizations namely in CPWD or State PWD.
- v) Scan Copy of PAN. (in pdf format)
- vi) Scan Copy of GST registration document. (in pdf format)
- vii) Scan copies of the document to prove the applicant has achieved a minimum annual value of turnover of 2.0 times estimated cost of the work. The annual turnover of each year of the last 3 years shall be more than the minimum annual turnover. Chartered Accountant certified profit and Loss account, Balance sheet to this effect to be enclosed (for example, if estimated cost is 5 Lakhs, then minimum annual turnover shall be 10 lakhs).
- viii) Scan copy of Details of civil Works completed during last three years ending last day of month previous to the one in which applications are invited should be either of the following:
- Three completed Civil works costing not less than the amount equal to 40(forty) percent of the estimated cost; or
- Two completed Civil works costing not less than the amount equal to 50 (fifty) percent of the estimated cost; or
- One completed civil work costing not less than the amount equal to 80(eighty) percent of the estimated cost;

#### Financial Bid:-

- The estimates are made by qualified engineers of the institute and base on latest CPWD-DSR with all updates and correction slips. Firms/ Contractors /Bidders should not quote too low high. To ensure quality materials, specification and workmanship, any tender with abnormally (+) or (-) percentage variation will be summarily rejected. So, the bidders must take due care while quoting.
- Evaluation criteria: Tender will be awarded to the lowest quoted Firm among those firms qualified in the technical bid. In case, two or more firms quote the same rates, then the tender will be awarded to the Firm which has got more average turnover in the last 3 years.

#### **Annexure-IV**

### **PROFORMA OF AGREEMENT**

(To be executed on a non-judicial stamp paper of Rs.100/- to be obtained by the bidder in its name)

### ICAR-CENTRAL INSTITUTE FOR RESEARCH ON COTTON TECHNOLOGY.

#### (INDIAN COUNCIL OF AGRICULTURAL RESEARCH)

ADENWALA ROAD, MATUNGA-19.

| ICAR-Central Institute for Research on Cotrepresentative (hereinafter referred to as the  | ton Technology, Matunga, Mumbai. (Employer) or his authorized the first party) and (Name of the contractor), S/O                 |
|---|--|
|   | e the works namely of(hereinafter referred to as the as the as and conditions.   |
| VHEREAS   |  |
|   | tte for Research on Cotton Technology, Matunga, Mumbai., hasfor appointment of contractor for the work as alled the "Work")      |
| B) The Contractor submitted their e-ten   | der for the aforesaid work vide tender no the contractor agreed to execute the work on the terms and                             |
|   | and this Agreement.  The of the aforesaid offer of the contractor, awarded the work to the Work order dated("LOA"/W.O)           |
| D) In pursuance of the LOA/W. O, the p<br>NOW, THEREFORE, the parties hereto he   | parties have agreed to enter into this Agreement. ereby agree as follows:  |
| The second party shall:   |  |
| <ol> <li>take up the works and arrange for</li> <li>employ suitable skilled person to</li> <li>regularly supervise and monitor</li> </ol> |  |
| 4. abide by the technical suggestion  | ns/direction of supervisory personnel of the first party. discrepancy to the notice of the representative of the first party and |
| 6. ensure that the work is carried or   | ut in accordance with scope  |
| of delay to be computed on per day basis<br>first party shall cancel the contract and ta<br>making any payment for the whatsoever         | the second party in completing the work within the   |
| ignature of the 1st Party   | Signature of the 2 <sup>nd</sup> Party   |
| Authority for ICAR-CIRCOT)  | (Contractor)   |
| Vitness: 1.   | Witness: 1.  |
| 2.  | 2.   |

FINANCIAL BID (Percentage BOQ) (This is only for reference. Fill up this excel format only given separately) NIT. No. 22 / E-Tenders-Works/ICAR-CIRCOT/2023-24

#### SCHEDULE "A": BILL OF QUANTITIES AND SCHEDULE OF WORKS:

NAME OF WORK: Yashwantrao Chavan Building- Renovation of Guest House room no. 10, Second floor of Yashwantrao Chavan Building at ICAR- CIRCOT, Matunga, Mumbai.

| Sr.<br>no | Item no<br>(As per<br>CPWD<br>DSR-21) | Description of Item  | Unit | Quantity |
|-----------|---------------------------------------|--|------|----------|
|           |                                       | Dismantling and Demolishing  |      |          |
| 1         | 15.2                                  | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix) | cum  | 1.00     |
| 2         | 15.3                                  | Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge.                               | cum  | 0.50     |
| 3         | 15.7                                  | Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.                         |      |          |
|           | 15.7.1                                | In cement mortar   | cum  | 5        |
| 4         | 15.12                                 | Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:   |      |          |
|           | 15.12.1                               |  |      |          |
|           |                                       | of area 3 sq. metres and below   | Each | 5        |
|           | 15.12.2                               | of area beyond 3 sq. metres  | Each | 1        |

| 5  | 15.23   | Dismantling tile work in floors and roofs laid in cement   |       |     |
|----|---------|--|-------|-----|
|    |         | mortar including stacking material within 50 metres lead.  |       |     |
|    |         |  |       |     |
|    | 15.23.1 | For thickness of tiles 10 mm to 25 mm sqm 60.50  | sqm   | 100 |
| 6  | 15.42   | Dismantling C.I. or asbestos rain water pipe with fittings   |       |     |
|    |         | and clamps including stacking the material within 50   |       |     |
|    |         | metres lead :  |       |     |
|    | 15.42.1 | 75 to 80 mm dia pipe metre   | Meter | 3   |
| 7  | 15.42.2 | 100 mm dia pipe  | Meter | 3   |
|    | 15.44   | Dismantling G.I. pipes (external work) including   |       |     |
| 8  |         | excavation and refilling trenches after taking out the pipes, manually/ by mechanical means including stacking |       |     |
|    |         | of pipes within 50 metres lead as per direction of   |       |     |
|    |         | Engineer-in-charge:  |       |     |
|    |         | 15.44.1 15 mm to 40 mm nominal bore  |       | 10  |
| 9  | 15.56   | Dismantling old plaster or skirting raking out joints and  | Metre |     |
|    | 15.50   | cleaning the surface for plaster including disposal of   |       |     |
|    |         | rubbish to the dumping ground within 50 metres lead.   | sqm   | 10  |
| 10 | 15.60   | Disposal of building rubbish / malba / similar   | ·     |     |
|    |         | unserviceable, dismantled or waste materials by  |       |     |
|    |         | mechanical means, including loading, transporting,   |       |     |
|    |         | unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial       |       |     |
|    |         | lead, for all leads including all lifts involved.  |       | 50  |
|    |         | Concrete Work  | cum   |     |
| 11 | 4.2     | Providing and laying cement concrete in retaining walls,   |       |     |
|    |         | return walls, walls (any thickness) including attached   |       |     |
|    |         | pilasters, columns, piers, abutments, pillars, posts, struts,  |       |     |
|    |         | buttresses, string or lacing courses, parapets, coping, bed  |       |     |
|    |         | blocks, anchor blocks, plain window sills, fillets, sunken   |       |     |

|    | 4.2.3 | floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:2:4 (1 Cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources) cum   | cum                | 1.0 |
|----|-------|--|--------------------|-----|
| 12 | 4.11  | Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20mm nominal size derived from natural sources).   | sqm                | 24  |
| 13 | 4.12  | Extra for providing and mixing water proofing material in cement concrete per 50kg work in doses by weight of cement as per manufacturer's specification. cement  Reinforced Cement Concrete   | Per 50Kg<br>cemrnt | 15  |
| 14 | 5.3   | Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement: 1.5 coarse sand(zone-III) derived from natural sources: 3 graded stone aggregate 20 mm nominal size derived from natural sources). | cum                | 0.5 |
| 15 | 5.9.5 | Centering and shuttering including strutting, propping etc. and removal of form for  Lintels, beams, plinth beams, girders, bressumers and cantilevers   | sqm                | 5   |
| 16 | 5.22A | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level.  | ·                  |     |

|    | •       |  | 1   | ,   |
|----|---------|--|-----|-----|
|    | 5.22A.3 | Cold twisted bars  | kg  | 30  |
|    |         | Brick Work   |     |     |
| 17 | 6.4     | Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :   |     |     |
|    |         | Cement mortar 1:4 (1 cement : 4 coarse sand )  |     | 2.5 |
|    | 6.4.1   |  | cum | 2.3 |
|    |         | HALF BRICK MASONRY   |     |     |
| 18 | 6.13    | Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.  Cement mortar 1:3 (1 cement :3 coarse sand) sqm  |     |     |
|    | 6.13.1  | 1043.10  | sqm | 30  |
| 19 | 6.15    | Extra for providing and placing in position 2 Nos 6mm dia. M.S. bars at every third course of half brick masonry.  | Sqm | 5   |
| 20 | 6.38    | Providing and laying autoclaved aerated cement blocks masonry with 100 mm thick AAC blocks in super structure above plinth level up to floor V level in cement mortar 1:4 (1 cement : 4 coarse sand ). The rate includes providing and placing in position 2 Nos 6 mm dia M.S. bars at every third course of masonry work. | Cum | 20  |
|    |         | Marble and Granite Work  |     |     |
| 21 | 8.2     | Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and  |     |     |

|    |         | texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.  Granite stone slab colour black or any shade |       |      |
|----|---------|--|-------|------|
|    | 8.2.2   | Area of slab upto 0.50 sqm sqm   |       |      |
|    | 8.2.2.1 | Area of slab over 0.50 sqm sqm   | Sqm   | 20   |
|    | 8.2.2.2 |  | sqm   | 10   |
| 22 | 8.4     | Extra for fixing marble /granite stone, over and above corresponding basic item, in facia and drops of width upto 150 mm with epoxy resin based adhesive, including cleaning etc. complete.  | metre | 1.0  |
| 23 | 8.5     | Extra for providing opening of required size & shape for wash basin/ kitchen sink in kitchen platform, vanity counter and similar location in marble/ Granite/ stone work, including necessary holes for pillar taps etc. including moulding, rubbing and polishing of cut edges etc. complete.  Wood and PVC Work               | each  | 4    |
| 24 | 9.1.1   | Providing wood work in frames of doors, windows,   | cum   | 0.22 |
|    |         | clerestory windows and other frames, wrought framed<br>and fixed in position with hold fast lugs or with dash<br>fasteners of required dia & length (hold fast lugs or dash<br>fastener shall be paid for separately).<br>Second class teak wood   |       |      |

| 25 | 9.21     | Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters:  35 mm thick including ISI marked Stainless Steel butt hinges with necessary screws | sqm   | 7.50 |
|----|----------|---|-------|------|
|    | 9.21.1   |   |       |      |
| 26 | 9.23     | Extra for providing lipping with 2nd class teak wood battens 25 mm minimum depth on all edges of flush door shutters (over all area of door shutter to be measured).  | sqm   | 7.5  |
| 27 | 8.24     | Providing and fixing expandable fasteners of specified size with necessary plastic sleeves and galvanised M.S. screws including drilling holes in masonry work /CC/ R.C.C. and making good etc. complete.  50 mm long   | each  | 12   |
|    | 8.24.4   |   |       |      |
| 28 | 9.40     | Providing and fixing wooden moulded beading to door and window frames with iron screws, plugs and priming coat on unexposed surface etc. complete:  |       |      |
|    |          | 2nd class teak wood   |       |      |
|    | 9.40.1   | 50x12 mm  |       | 20   |
|    | 9.40.1.1 |   | metre |      |
| 29 | 9.53     | Providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bolts, nuts  | each  | 8    |

|    |                            | and wooden plugs and embedding in cement concrete block 30x10x15cm 1:3:6 mix (1 cement : 3 coarse sand : 6 graded stone aggregate 20mm nominal size).   |                      |             |
|----|----------------------------|---|----------------------|-------------|
| 30 | 9.82                       | Providing and fixing bright finished brass hanging type floor door stopper with necessary screws, etc. complete.  | each                 | 3           |
| 31 | 9.83                       | Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS: 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete. | each                 | 3           |
| 32 | 9.92                       | Providing and fixing chromium plated brass handles with necessary screws etc. complete:  125 mm   |                      |             |
|    | 9.92.1<br>9.92.2<br>9.92.3 | 100 mm<br>75 mm   | each<br>each<br>each | 3<br>3<br>3 |
| 33 | 9.96                       | Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete:   |                      |             |
|    | 9.96.1<br>9.96.2           | 300x16 mm<br>250x16 mm  | each<br>each         | 3<br>3      |
| 34 | 9.97                       | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete  |                      |             |
|    | 9.97.3                     | 200x10 mm   | each                 | 3           |

|    | 9.97.4<br>9.97.5   | 150x10 mm<br>100x10 mm   | each<br>each | 3<br>3 |
|----|--------------------|--|--------------|--------|
|    | 3.37.3             | TOOX TO THIN   | eacii        | 3      |
| 35 | 9.100              | Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete: 125 mm 125 mm  |              |        |
|    | 9.100.1            | 100 mm   |              | _      |
|    | 9.100.2<br>9.100.3 | 75 mm  | each         | 3      |
|    | 9.100.5            |  | each<br>each | 3      |
| 36 | 9.101              | Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.  |              |        |
|    | 9.101.1            | Single rubber stopper  | Each         | 3      |
| 37 | 9.114              | Providing and fixing magnetic catcher of approved quality in cupboard / ward robe shutters, including fixing with necessary screws etc. complete.  Triple strip vertical type  |              |        |
|    | 9.114.1            | Triple surp vertical type  | Each         | 6      |
| 38 | 9.127              | Providing & Fixing decorative high pressure laminated sheet of plain / wood grain in gloss / matt/ suede finish with high density protective surface layer and reverse side of adhesive bonding quality conforming to IS: 2046 Type S, including cost of adhesive of approved quality. |              |        |

|    | 9.127.1 | 1.5 mm thick   | sqm | 15.0  |
|----|---------|--|-----|-------|
|    |         | Flooring   |     |       |
| 39 | 11.3    | Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete.   |     |       |
|    | 11.3.1  | 40 mm thick with 20 mm nominal size stone aggregate  | sqm | 10    |
|    |         | Ceramic Glazed Tiles   |     |       |
| 40 | 11.37A  | Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS: 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. | sqm | 100.0 |
| 41 | 11.38   | Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in all colours, shades, except White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick bed of cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sq.m including pointing the joints with white cement and matching pigments etc., complete.   | sqm | 30    |
|    |         | Vitrified Floor Tiles  |     |       |
| 42 | 11.41   | Providing and laying vitrified floor tiles in different sizes  |     |       |

|    | 11.41.2 | (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.  Size of Tile 600x600 mm   | 0000 | 42 |
|----|---------|--|------|----|
| 43 | 11.41.2 | Deduct for not using 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand) bedding in laying of floor tiles and jointing with grey cement slurry @ 3.3 kg/ sqm.   | sqm  | 10 |
| 44 | 11.43   | Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, in average 3mm thickness.   | sqm  | 10 |
| 45 | 11.46   | Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joint with white cement & matching pigments etc. complete. |      |    |
|    | 11.46.2 | Size of Tile 600x600 mm  | sqm  | 4  |
|    |         | Roofing  |      |    |
| 46 | 12.54.2 | Providing and fixing Gl Clip in Metal Ceiling System of 600x600 mm module which includes providing and fixing 'C' wall angle of size 20x30x20 mm made of 0.5 mm thick pre painted steel along the perimeter of the room with help of nylon sleeves and wooden screws at 300 mm   | sqm  | 65 |

|    |            | center to centre, suspending the main C carrier of size 10x38x10 mm made of G.I steel 0.7 mm thick from the soffit with help of soffit cleat 37x27x25x1.6 mm, rawl plugs of size 38x12 mm and C carrier suspension clip and main carrier bracket at 1000 mm c/c. Inverted triangle shaped Spring Tee having height of 24 mm and width of 34 mm made of Gl steel 0.45 mm thick is then fixed to the main C carrier and in direction perpendicular to it at 600 mm centers with help of suspension brackets. Wherever the main C carrier and spring T have to join, C carrier and spring T connectors have to be used. All sections to be galvanized @ 120 gms/sqm (both side inclusive), fixing with clip in tiles into spring T with: GI Metal Ceiling Clip in plain Beveled edge global white color tiles of size 600x600 and 0.5 mm thick with 25 mm height, made of G I sheet having galvanizing of 100 gms/sqm (both sides inclusive) and 20% perforation area with 1.8 mm dia holes and having NRC of 0.5, electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after bending and perforation. |         |     |
|----|------------|--|---------|-----|
|    |            | Finishing  |         |     |
| 49 | 13<br>13.6 | CEMENT PLASTER (IN COARSE SAND) 20 mm cement plaster of mix:   |         |     |
|    | 13.6.1     | 1:4 (1 cement: 4 coarse sand)  | sqm     | 150 |
| 50 |            | Extra for providing and mixing water proofing material in  | Per bag | 150 |
| 30 | 13.21      | cement plaster work in proportion recommended by the   | of 50kg |     |
|    |            | manufacturers.   | cement  |     |
|    |            |  | used in |     |
|    |            | 10   | the mix | 10  |
| 51 | 13.12      | 18 mm cement plaster in two coats under layer 12 mm  | Sqm     | 30  |

|      | 1       |   |       | 1   |
|------|---------|---|-------|-----|
|      |         | thick cement plaster 1:5 (1 cement : 5 coarse sand) and a top layer 6 mm thick cement plaster 1:3 (1 cement : 3 coarse sand) finished rough with sponge.  |       |     |
| 52.1 | 14.75   | Repair to plaster of thickness 12mm to 20 mm in patches of area 2.5 sqm and under, including cutting the patch in proper shape, raking out joints and preparing plastering the wall surface with white cement based polymer modified self-curing mortar, including disposal of rubbish, all complete as per the direction of Engineer-In-Charge.  | Sq.mt | 10  |
| 52   | 13.22   | Extra for plastering exterior walls of height more than 10 m from ground level for every additional height of 3 m or part thereof.  | Sqm   | 6   |
| 53   | 13.26   | Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.   | Sqm   | 30  |
| 54   | 13.78   | Providing and applying 12 mm thick (average) premixed formulated one coat gypsum lightweight plaster having additives and light weight aggregates as vermiculite/perlite respectively conforming to IS: 2547 (Part – 1 & II) 1976, applied on hacked / uneven background such as bare brick/ block/ RCC work on walls & ceiling at all floors and locations, finished in smooth line and level etc. complete. | Sqm   | 85  |
| 55   | 13.80   | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.   | Sqm   | 30  |
| 56   | 13.85   | Applying priming coats with primer of approved brand and manufacture, having low VOC (Volatile Organic Compound) content.  With water thinnable cement primer on wall surface   |       | 100 |
|      | 13.85.3 | having VOC content less than 50 grams/litre   | sqm   | 180 |

| 57 | 13.61.1        | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  Two or more coats on new work  (A sign points A poolity first quality)   | sqm  | 252 |
|----|----------------|---|------|-----|
|    |                | (Asian paints Apcolite first quality)  Repairs to Building  |      | 260 |
| 58 | 14.1.2<br>14.2 | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  With cement mortar 1:4 (1cement: 4 coarse sand)  Fixing chowkhats in existing opening including embedding chowkhats in floors or walls cutting masonry for holdfasts, embedding hold fasts in cement concrete blocks of size 15 x 10 x 10 cm with cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size), painting two coats of approved wood preservative to sides of chowkhats and making good the damages to walls and floors as required complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  Door chowkhats | sqm  | 1   |
|    | 14.2.1         |   |      |     |
|    |                |   | each | 2   |
|    | 14.3           | Fixing chowkhat in existing opening in brick/ RCC wall with dash fasteners/Chemical fasteners of appropriate size (3 nos on each vertical member of door chowkhat and 2 nos on each vertical member of window chowkhats),   |      |     |

|    |        | including Cost of dash fasteners/ chemical fastener.  |      |      |
|----|--------|---|------|------|
|    |        | Making the opening in brick masonry including dismantling in floor or walls by cutting masonry and  | Each | 2    |
|    | 14.4   | making good the damages to walls, flooring and jambs complete, to match existing surface i/c disposal of mulba/rubbish to the nearest municipal dumping ground, all complete as per direction of Engineer-in-Charge.  | sqm  | 2    |
|    | 14.4.1 | For door/ window/ clerestory window   |      |      |
|    |        | Sanitary Installations  |      |      |
| 59 | 15.9   | Providing and fixing white vitreous china Under counter wash basin of size 480 x 365 X 200 mm of Jaguar continental series or equivalent (Model No: CNS-WHT-701) with tap hole of required size as per Architectural Drawing and as directed by the Engineer in charge. | No's | 3.00 |
| 60 | 15.15  | Providing and fixing of Swivel Towel Holder Twin Type of jaguar bath accessories Continental series (Item Code No. ACN-1115S) etc. complete as per the directions of Engineer - in - charge.  | No's | 2.00 |
| 61 | 15.13  | Providing and fixing of Toilet Roll Holder with stainless steel flap of Jaguar Bath Accessories Continental series (Item Code No.: AKP 35753PS) etc. complete as per the direction of Engineer in charge.   | No's | 2.00 |
| 62 | 15.14  | Providing and fixing of soap Dispenser with Glass Bottle of jaguar Bath Accessories Continental series (Item Code No. ACN-1135N) etc. complete as per the directions of Engineer - in -charge.  | No's | 2.00 |
| 63 | 15.15  | Providing and fixing of Swivel Towel Holder Twin Type of jaguar bath accessories Continental series (Item Code No. ACN-   | No's | 2.00 |

|    |         | 1115S) etc. complete as per the directions of Engineer - in - charge.  |      |      |
|----|---------|--|------|------|
| 64 | 15.16   | Providing and fixing C.P Brass two way bib cock with wall flange (Item Code: KUP - 35041PM) of Jaguar Kubix prime turn series or equivalent etc. complete as per the directions of Engineer - in - charge.   | No's | 4.00 |
| 65 | 15.17   | Providing and fixing C.P Brass one way bib cock with wall flange (Item Code: KUP - 35037PM) of Jaguar Kubix prime turn series or equivalent etc. complete as per the directions of Engineer - in - charge.   | No's | 6.00 |
| 66 | 15.18   | Providing and fixing C.P brass Pillar tap (Item Code: KUP - 35001PM) of Jaguar Kubix prime turn series or equivalent etc. complete as per the directions of Engineer - in - charge.  | No's | 3.00 |
| 67 | 15.19   | Providing and fixing beveled edge mirror of superior glass (of Approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats / frame with CP brass mirror screws and washers complete as directed by the Engineer in Charge.  6 MM thick | No's | 2    |
| 68 | 15.20   | Providing and fixing C.P Brass click clack waste coupling 32 mm size full thread with 80 mm Height of Jaguar allied series (Model No: ALD-727) or equivalent as per directions of Engineer in Charge.  | No's | 4.00 |
| 69 | 15.21   | Providing and fixing white vitreous china extended wall mounting water closet of approved shape including soft close seat cover, nuts, bolts & gasket etc complete.  | No's | 2.00 |
|    | 15.21.1 | Wall hung WC with UF Soft close seat cover, Hinges Accessories   |      |      |

|    |  | set, size -355x 585 X 410 mm of Jaguar OPAL series (Model No: OPS- WHT-15951)  |              |        |
|----|--|--|--------------|--------|
| 70 | 15.22  | Providing and fixing Jaquar make Allied series C. P. brass 32 mm size bottle trap (with internal partition) with 300 mm & 190 mm long wall connection pipes & wall flange (Code No. ALD - 769L300 x 190) as per direction of Engineer - in - charge. | No's         | 3.00   |
| 71 | 15.23  | Providing and fixing 450 mm long braided hose with two 15mm nuts & rubber washer without nipple (Suitable for Geysers) of Jaguar make Allied Series (Item Code No: ALD-805B) or equivalent as per the directions of Engineer in Charge.              | No's         | 2.00   |
| 72 | 15.24  | Providing and fixing C.P brass Angular stop cock with wall flange of approved quality Jaguar make Kubix Prime series (Item Code: KUP-35053 PM) or equivalent   | No's         | 2.00   |
| 73 | 17.34<br>17.34.1                             | Providing and fixing toilet paper holder:<br>C.P. brass  | each         | 2      |
| 74 | 17.28.1<br>17.28.1.1<br>17.28.1.2<br>17.28.2 | Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.  Semi rigid pipe  32mm dia 40mm dia  Flexible pipe 32mm dia  | Each<br>Each | 2<br>4 |
|    | 17.28.2.1<br>17.28.2.2<br>17.28.2.2          | 40mm dia   | Each<br>Each | 2<br>2 |

| 75 | 17.35                           | Providing and fixing soil, waste and vent pipes:  |       |    |
|----|---------------------------------|---|-------|----|
|    | 17.35.1                         | 100 mm dia  |       |    |
|    | 17.35.1.1                       | Sand cast iron S&S pipe as per IS: 1729   | Metre | 20 |
|    | 17.35.2                         | 75 mm diameter :  |       |    |
|    | 17.35.2.1                       | Sand cast iron S&S pipe as per IS: 1729   | Metre | 20 |
| 76 | 17.36                           | Providing and filling the joints with spun yarn, cement slurry and cement mortar 1:2 (1 cement : 2 fine sand) in S.C.I./ C.I. Pipes : 75 mm dia pipe each |       |    |
|    | 17.36.1                         |   | Each  | 5  |
|    | 17.36.2                         | 100 mm dia pipe each  |       | 5  |
| 77 | 17.38                           | Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete.                               |       |    |
|    | 17.38.1                         | 100mm dia pipe<br>Sand cast iron S&S as per IS – 1729   |       |    |
|    | 17.38.1.1                       | 75mm dia pipe   |       | 6  |
|    | 17.38.2<br>17.38.2.1            | Sand cast iron S&S as per IS – 1729   | each  | 6  |
| 78 | 17.42                           | Providing and fixing double equal plain junction of required degree.  |       |    |
|    | 17.42.1<br>17.42.1.1<br>17.42.2 | 100x100x100x100 mm<br>Sand cast iron S&S as per IS - 1729<br>75x75x75x75 mm   | each  | 3  |

|    | 17.42.2.1          | Sand cast iron S&S as per IS - 1729  | each         | 3        |
|----|--------------------|--|--------------|----------|
| 79 | 17.59              | Providing and fixing M.S. stays and clamps for sand cast iron/ centrifugally cast (spun) iron pipes of diameter  |              |          |
|    | 17.59.1<br>17.59.2 | 100 mm<br>75mm   | Each<br>each | 10<br>10 |
| 80 | 17.70              | Providing and fixing PTMT Bottle Trap for Wash basin and sink  |              |          |
|    | 17.70.1            | Bottle trap 31mm single piece moulded with height of 270 mm, effective length of tail pipe 260 mm from the centre of the waste coupling, 77 mm breadth with 25 mm minimum water seal, weighing not less than 260 gms   | each         | 2        |
| 81 | 17.70.2            | Bottle trap 38 mm single piece moulded with height of 270 mm, effective length of tail pipe 260 mm from the centre of the waste coupling, 77 mm breadth with 25 mm minimum water seal, weighing not less than 263 gms each 325.10  | each         | 2        |
| 82 | 17.77              | Providing and fixing M.S. holder bat clamp of approved design to sand cast iron/ cast iron (spun) pipes comprising of M.S. flat brackets made of 50x5 mm flat of specified shape, projecting 75 mm outside the wall surface and fixed on wall with 4nos, 6mm dia expansion hold fasteners, including drilling necessary holes in brick wall/ CC/ RCC surface and the cost of bolts etc. The pipes shall be fixed to the already fixed brackets with the help of 30 mm x1.6 mm galvanised M.S. flats of specified shape and of total length 420 mm and shall be fixed with M.S. nuts, bolts, & washers of size 25x6 mm, one bolts on each side of the pipe. |              |          |

|    | 17.77.1 | Total bracket length 580 mm of approved shape and design (for single 100 mm dia pipe)  | each           | 6  |
|----|---------|--|----------------|----|
| 83 | 17.77.2 | Total bracket length 810 mm of approved shape and design (for two 100 mm dia pipes)  | each           | 6  |
|    |         | Water Supply   |                |    |
| 84 | 18.7    | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work Exposed on wall   |                |    |
|    | 18.7.1  | 15 mm nominal dia Pipes  | Meter          | 5  |
|    | 18.7.2  | 20 mm nominal dia Pipes  | Meter          | 6  |
|    | 18.7.3  | 25 mm nominal dia Pipes<br>32 mm nominal dia Pipes   | Meter<br>Meter | 5  |
|    | 18.7.4  | 40 mm nominal dia Pipes  | Meter          | 5  |
| 85 | 18.7.5  | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. |                | 10 |

|    | 18.8.1                      | 15 mm nominal dia Pipes metre   | Meter | 10 |
|----|-----------------------------|---|-------|----|
|    | 18.8.2                      | 20 mm nominal dia Pipes metre   | Meter | 8  |
| 86 | 18.21                       | Providing and fixing uplasticised PVC connection pipe with brass unions:  |       |    |
|    | 18.21.2<br>18.21.2.1        | 45 cm length<br>15 mm nominal bore  | each  | 15 |
| 87 | 18.22                       | Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet:   |       |    |
|    | 18.22.1                     | 100 mm diameter each  | Each  | 2  |
|    | 18.22.2                     | 150 mm diameter each  | Each  | 1  |
| 88 | 18.17                       | Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end):  |       |    |
|    | 18.17.3                     | 40 mm nominal bore  | each  | 2  |
| 89 | 18.50                       | Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms.  15 mm nominal bore                   | each  | 2  |
| 90 | 18.50.1<br>18.52<br>18.52.1 | Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931.  15 mm nominal bore                                    | each  | 2  |
| 91 | 18.53                       | Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931  15mm nominal bore                                  |       |    |
| 02 | 18.53.1                     | Cutting heles we to 15v15 and in D.C.C. floorer 1   | each  | 10 |
| 92 | 18.77                       | Cutting holes up to 15x15 cm in R.C.C. floors and roofs for passing drain pipe etc. and repairing the hole after insertion of drain pipe etc. with cement concrete 1:2:4 (1 | each  | 3  |

| nominal size), including finishing complete so as to make it leak proof.  Drainage: Stone ware pipes and fittings  19.1 Providing, laying and jointing glazed stoneware pipes class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete  19.1.2 metre  19.2 Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per standard design :  150 mm diameter S.W. pipe  19.2.2 metre  3  95 19.4 Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm |    |        |   | l     |   |
|--|----|--------|---|-------|---|
| 93 19.1 Providing, laying and jointing glazed stoneware pipes class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete  150 mm diameter  19.1.2 Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per standard design :  150 mm diameter S.W. pipe  19.2.2 metre  3  95 19.4 Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm  |    |        |   |       |   |
| class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. complete  150 mm diameter  19.1.2  Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per standard design :  150 mm diameter S.W. pipe  19.2.2  Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm  |    |        | Drainage: Stone ware pipes and fittings   |       |   |
| 19.1.2 Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per standard design :  150 mm diameter S.W. pipe  19.2.2 Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm   | 93 | 19.1   | class SP-1 with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including  |       |   |
| 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per standard design :  150 mm diameter S.W. pipe  19.2.2  Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm   |    | 19.1.2 | 150 mm diameter   | metre | 3 |
| 19.2.2  Providing and fixing square-mouth S.W. gully trap class SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm  | 94 | 19.2   | 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) all-round S.W. pipes including bed concrete as per  |       |   |
| SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm  |    | 19.2.2 | 150 mm diameter S.W. pipe   | metre | 3 |
| kg and frame to be not less than 2.70 kg as per standard design: 100x100 mm size P type  | 95 | 19.4   | SP-1 complete with C.I. grating brick masonry chamber with water tight C.I. cover with frame of 300 x300 mm size (inside) the weight of cover to be not less than 4.50 kg and frame to be not less than 2.70 kg as per standard design: |       |   |
| 19.4.1 With common burnt clay F.P.S. (non modular) bricks of class designation 7.5   |    |        | · · · · · · · · · · · · · · · · · · ·   | each  | 1 |
| 96 19.21 Making connection of drain or sewer line with existing manhole including breaking into and making good the  | 96 | 19.21  |   |       |   |

|    |          | walls, floors with cement concrete 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) cement plastered on both sides with cement mortar 1:3 (1 cement : 3 coarse sand), finished with a floating coat of neat cement and making necessary channels for the drain etc. complete :  |      |    |
|----|----------|---|------|----|
|    | 19.21.1  | For pipes 100 to 250 mm diameter  | each | 2  |
|    |          | Aluminium Work  |      |    |
| 97 | 21.1     | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately):  For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) |      |    |
|    | 21.1.1   |   | kg   | 40 |
| 98 | 21.1.1.1 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural   |      |    |

|     |        | drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)   |           |         |
|-----|--------|--|-----------|---------|
|     | 21.3.2 |  |           | -       |
| 99  | 21.5   | Providing and fixing powder coated aluminium work (minimum thickness of powder coating 50 micron) consisting of tee/ angle sections, of approved make conforming to IS: 733 in frames of false ceiling including aluminium angle cleats with necessary C.P. brass/ stainless steel sunk screws, aluminium perimeter angles fixed to wall with stainless steel rawl plugs @ 450 mm centre to centre and fixing the frame work to G.I. level adjusting hangers 6 mm dia. with necessary cadmium plated machine screws all complete as per approved architectural drawings and direction of the Engineer-incharge (level adjusting hangers, ceiling cleats and expansion hold fasteners to be paid for separately). | sqm<br>kg | 5<br>15 |
| 100 | 21.6   | Providing and fixing 6 mm dia. G.I. level adjusting hangers (upto 1200mm length), fixed to roof slabs by means of ceiling cleats made out of G.I. flat 40x3mm size 60 mm long and stainless steel expandable dash fastener of 12.5 mm dia and 50 mm long, complete as per direction of Engineer-in-charge.  Filling the gap in between aluminium frame & adjacent  | each      | 12      |
|     | 22.0   | RCC/ Brick/ Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-incharge complete.   |           |         |

|     | 21.8.1 | Upto 5mm depth and 5 mm width  | metre | 10 |
|-----|--------|--|-------|----|
| 102 | 21.14  | Providing and fixing anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868. Minimum anodic coating of grade AC 15) sub frame work for windows and ventilators with extruded built up standard tubular sections of approved make conforming to IS: 733 and IS: 1285, fixed with dash fastener of required dia and size (Dash fastener to be paid for separately).  | kg    | 5  |
| 103 | 21.17  | Providing and fixing anodised aluminium grill (anodised transparent or dyed to required shade according to IS: 1868 with minimum anodic coating of grade AC 15) of approved design/pattern, with approved standard section and fixed to the existing window frame with C.P. brass/stainless steel screws @ 200 mm centre to centre, including cutting the grill to proper opening size for fixing and operation of handles and fixing approved anodised aluminium standard section around the opening, all complete as per requirement and direction of Engineer-in-charge. (Only weight of grill to be measured for payment). | kg    | 3  |
| 104 | 22.5   | Water Proofing  Providing and laying water proofing treatment in sunken  |       |    |
|     |        | portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying: (a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours. (b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be allowed to air cure for 4  | sqm   | 15 |

|     |    | hours followed with water curing for 48 hours. The rate includes preparation of surface, treatment and sealing of all joints, corners, junctions of pipes and masonry with polymer mixed slurry.  |      |   |   |
|-----|----|---|------|---|---|
| 105 | MR | Providing and fixing castr iron nahani trap/floor trap of 100mm inlet and 75mm outlet (weighing 5.80kg each) joining with lead with connection pipes, placing as per the drawing, embedding in cement concrete 1:2:4 and making pressure and fixing 1no 120 m dia C.P Brass grating, complete all specification and drawings ans as directed at site.   | Each |   | 3 |
| 106 | MR | Providing and fixing heavy quality C.P brass sink cock  |      |   |   |
|     |    | (table mounted model) of as per requirement and sample.   | Each |   | 6 |
| 107 | MR | Providing and Laying bricks bats with mortar using broken bricks/bricks bats 25 mm to 115 mm size with 50% of cement mortar 1:5 (1 cement : 5 coarse sand) admixed with water proofing compound conforming to IS:2645 and approved by Engineer-in-charge over 20 mm thick layer of cement mortar of mix 1:5 (1 cement: 5 coarse sand) admixed with water proofing compound conforming to IS:2645 and approved by Engineer-Incharge to required slope and treating similarly and adjoining walls upto 300 mm height including rounding of junctions of walls and slabs c) After two days of proper curing applying a second coat of cement slurry using 2.75 kg/sqm of cement admixed jointless cement mortar of mix 1:4 (1 cement : 4 coarse sand) admixed with water proofing compound conforming to IS: 2645 and approved by Engineer-In-Charge. Finishing and surface with 20 mm thick joint less cement mortar of mix 1:4 (1 cement: 4 coarse sand) admixed with water proofing compound conforming to IS: 2645 and approved by | Sqm  | 8 |   |

|     |    |   |       | 1  |
|-----|----|---|-------|----|
|     |    | Engineer in charge including finishing the surface with trowel with neat cement slurry. The whole area so finished shall be flooded with water for a minimum period of two weeks for curing and for final test. All above operations to be done in order and as directed and specified by Engineer Incharge in his presence only.   |       |    |
| 108 | MR | Providing waterproofing treatment to gaps around pipe inserts by using double sided adhesive bituminous Dr. 98Fixit Bath seal tape to be warped around pipe inserts. The gaps are then filled using non-shrink, cementitious "Dr.Fixit Bath sea Grout" as per directions mentioned in manual and Engineer Incharge, including all materials, labour, lead or lift etc. complete. This item shall be carried out in presence of Engineer Incharge. | Each  | 6  |
| 109 | MR | Providing waterproofing to Gaps around Nahani trap by filling the gaps with self leveling Non-shrink cementitious "Dr. Fixit Bath sea Grout" to reduce the risk of cracking and seepage. This item shall be carried out in presence of Engineer Incharge.   | Each  | 4  |
| 110 | MR | Providing waterproofing to sunken portion of floor area of bathroom by treating with two coats of polymer modified cementitious, elastromeric water proof coating of Dr. Fixit Bath seal WPC" to achieve 1 mm thick coating having high elongation and impermeable to ingress of water as per instruction in the manual and direction. This item shall be carried out in presence of Engineer incharge.   | Sqm   | 15 |
| 111 | MR | Providing and laying waterproofing Angle fillet prepared with Dr. Fixit pidicrete UPR Latex along the junctions of walls and slabs. The junction is reinforced with a woven glass fibre mesh between the first and second coats of Dr. Fixit Bathseal WPC coating as per the direction of the   | Meter | 20 |

|     |    | Engineer incharge in his presence  |       |    |
|-----|----|--|-------|----|
| 112 | MR | Providing waterproofing on the walls of splash zone area of bathroom (shower area) to prevent water seepage through the walls through tile joints which leads to dampness on the walls adjoining the bathroom, by treating with two coats of polymer modified cementitious, elastrometric water proof coating of Dr.Fixit Bath seal WPC" up to height of 1800 mm to achieve 1 mm thick coating having high elongation and impermeable to ingress of water as per instruction in the manual and direction of the Engineer Incharge, including all material and labour etc. complete. This item shall be carried out in presence of Engineer Incharge. | Sqm   | 80 |
| 113 | MR | Providing waterproofing to Gaps around sanitary wares by filling the gaps with "Dr.Fixit Bath seal sealant" to reduce the risk of shrinkage, cracking over time with usage to remain clean surface without stains. This items shall be carried out in presence of Engineer Incharge.   | Meter | 10 |
| 114 | MR | Providing and fixing Good Quality, heavy duty Hot and Cold water C.P. Mixer in the Bathrooms as per direction of the Engineer incharge   | Each  | 3  |
| 115 | MR | Providing and fixing good quality ceramic 12"x3" Boarder tiles using Cement mortar 1:3 (1 Cement: 3 Coarse sand), 12 mm thick as per requirement design and as per direction of Engineer incharge  | Meter | 15 |
| 116 | MR | Providing and fixing colour ceramic counter top wash basin of size 550x 400 mm on the granite slab counter, with 34 mm C.P. brass waste of standard pattern including all material, labour, tools etc. complete as per directions of the Engineer incharge.  | Each  | 6  |
| 117 | MR | Providing and fixing Heavy duty Brass aldrops of Size 300 mm length as per required design, colur with all Nut   | Each  | 4  |

|     |    | and bolts as per directions                              |      |    |
|-----|----|--|------|----|
| 118 | MR | Providing and fixing Heavy duty CP Towel rods 600 mm     | Each | 3  |
|     |    | length with all necessary brass screws as per directions |      |    |
| 119 | MR | Providing and spreading POP slurry over the existing     | Sqm  | 55 |
|     |    | vitreous flooring to protect from damage during the      |      |    |
|     |    | renovation work and removing the same after completion   |      |    |
|     |    | of work to the original state as per directions.         |      |    |

Total Amount (Rs.) :- 13,63,194.00

Sujatha Koshy Senior Administrative Officer